GALLEGAS by CUPA

UK CA

DECLARATION OF PERFORMANCE (No.2025/03)

No. 31

1. Identification of the product-type		**Slate GALLEGAS by CUPA 37**
2. Type of slate		Non carbonated slate originated by tectonic compression
3. Quarry		San Vicente,Villamartín de Valdeorras, Ourense
4. Sizes	2ª	60x45, 60x30,50x45, 50x38,50x30, 50x25,46x30,45x33,45x22,40x38,40x30, 40x25, 40x20, 32x22, 30x20, 27x18, 25x18
5. Intented uses of the product		Slates for discontinuos roofing an external cladding (UNE-EN 12326-1)
6. Name and address of the representative		SIG Trading, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH. e-mail: gallegas@cupapizarras.com Phone: +34 988 300 006
7. System of assessment of performance		System 4

8. Declared performance

ESSENTIAL CARACTERISTICS	PERFORMANCE				HARMONISED STANDARD
Deviation from declared length and width	Complies: < ±5mms				EN 12326-1
Deviation from squareness	Complies: <±1%				EN 12326-1
Deviation from straightness of edges	Complies: <±1%				EN 12326-1
Slate type for deviation from flatness	**Very Flat**	**Flat**	**Normal**	**Non flat**	**EN 12326-1**
Deviation from flatness		X			EN 12326-1
Slate type for the calculation of the packaged slate thickness	**Very smooth**	**Smooth**	**Normal**	**Texturised**	**EN 12326-1**
Nominal thickness and variation	3,7 (±25%) mm 5 (±35%) mm 6,5 (±35%) mm				EN 12326-1
Characteristicsss modulus of rupture	**Transverse**	**42 MPA**	**Longitudinal**	**46 MPA**	**EN 12326-1**
Water absorption	0,06%	Code: W1 (< 0,6%)			EN 12326-1
Freeze thaw test		Fulfill: < 0,6%			EN 12326-1
Thermal cycle test	T1				EN 12326-1
Apparent calcium carbonate content	0,07%	Complies: (< 20%)			EN 12326-1
SO2 exposure test	S1				EN 12326-1
Non carbonate carbon content	0,40%	Complies: (< 2%)			EN 12326-1
External fire exposure / Reaction to fire	Deemed to satisfy, class Broof / Clase A1				EN 12326-1
Dangerous substances emission	None in conditions of use as roofing or external cladding				EN 12326-1
Sustainability	DAPcons®				ISO 14025/ISO21930

*** The performance of the product identified in point 1 and 2, is in conformity with the declared performance in table 8**

*** This declaration is sole responsability of the manufacturer identified in point 6**

Signed on behalf of the manufacturer by the Quality Manager

Sobradelo de Valdeorras, March 24, 2025
Juan López